



### Benefits

- ▶ 7U 19" widescreen LCD display panel
- ▶ 1440 x 900 native resolution / 16.7M colors / 1000 cd/m² brightness
- ▶ DVI-D + VGA video input
- ▶ 2-year standard warranty ( upgradable up to 5 years )

### Options

- HDMI 1.2 video input
- 3G / HD / SD-SDI Broadcast-grade input
- S-Video + Composite ( BNC )
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MCS Multi display OSD controller
- MIL-type or lockable connector
- Touchscreen : Capacitive 1-pt / Resistive 1-pt

## Product Specifications

Video	
Video input	VGA + DVI-D single link

Video Option		
Digital	HDMI	HDMI 1.2 / HDCP 1.1
Analog	S-Video ( 4-pin )	NTSC & PAL
	Composite ( BNC )	NTSC & PAL

LCD Panel	
Panel size ( diagonal )	19"
Native resolution	1440 x 900
Brightness ( cd/m² )	1000
Contrast ratio ( typ. )	1000 : 1
Colors	16.7 M
Viewing angle ( L/R/U/D )	80/80/80/80
Response time ( ms )	5
Dot pitch ( mm )	0.2835
Display area ( mm )	408.24H x 255.15V
Surface treatment	Haze 25%, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF ( hrs )	30,000

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant

Physical		
Dimensions ( W x D x H )	Product	480 x 58 x 310 mm 18.9 x 2.3 x 12.2 inch
	Packing	529 x 124 x 451 mm 20.8 x 4.9 x 17.8 inch
Weight	Net	5.8 kg / 12.8 lb
	Gross	7.9 kg / 17.4 lb

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption	Screen on	Max. 35W
	Power saving mode	Max. 4W
	Power button on	Max. 1W

### Diagrams ( mm )

