



AVSC-HDMI-VIDEO

HDMI to Video Scaler and Converter

Converts digital HDMI and audio to component/CVBS video with either digital audio (S/PDIF) or analog stereo audio.



Customer Support Information

Order toll-free in the U.S.: Call 877-877-BBOX (outside U.S. call 724-746-5500) • FREE technical support 24 hours a day, 7 days a week: Call 724-746-5500 or fax 724-746-0746 • Mailing address: Black Box Corporation, 1000 Park Drive, Lawrence, PA 15055-1018
Web site: www.blackbox.com • E-mail: info@blackbox.com

Trademarks Used in this Manual

Trademarks Used in this Manual

Black Box and the Double Diamond logo are registered trademarks of BB Technologies, Inc.

HDMI is a registered trademark of HDMI Licensing LLC.

Any other trademarks mentioned in this manual are acknowledged to be the property of the trademark owners.

Disclaimer

Black Box Network Services shall not be liable for damages of any kind, including, but not limited to, punitive, consequential or cost of cover damages, resulting from any errors in the product information or specifications set forth in this document and Black Box Network Services may revise this document at any time without notice.

FEDERAL COMMUNICATIONS COMMISSION AND INDUSTRY CANADA RADIO FREQUENCY INTERFERENCE STATEMENTS

This equipment generates, uses, and can radiate radio-frequency energy, and if not installed and used properly, that is, in strict accordance with the manufacturer's instructions, may cause interference to radio communication. It has been tested and found to comply with the limits for a Class A computing device in accordance with the specifications in Subpart B of Part 15 of FCC rules, which are designed to provide reasonable protection against such interference when the equipment is operated in a commercial environment. Operation of this equipment in a residential area is likely to cause interference, in which case the user at his own expense will be required to take whatever measures may be necessary to correct the interference.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This digital apparatus does not exceed the Class A limits for radio noise emission from digital apparatus set out in the Radio Interference Regulation of Industry Canada.

Le présent appareil numérique n'émet pas de bruits radioélectriques dépassant les limites applicables aux appareils numériques de classe A prescrites dans le Règlement sur le brouillage radioélectrique publié par Industrie Canada.

Normas Oficiales Mexicanas (NOM) Electrical Safety Statement INSTRUCCIONES DE SEGURIDAD

1. Todas las instrucciones de seguridad y operación deberán ser leídas antes de que el aparato eléctrico sea operado.
2. Las instrucciones de seguridad y operación deberán ser guardadas para referencia futura.
3. Todas las advertencias en el aparato eléctrico y en sus instrucciones de operación deben ser respetadas.
4. Todas las instrucciones de operación y uso deben ser seguidas.

NOM Statement

5. El aparato eléctrico no deberá ser usado cerca del agua—por ejemplo, cerca de la tina de baño, lavabo, sótano mojado o cerca de una alberca, etc.
6. El aparato eléctrico debe ser usado únicamente con carritos o pedestales que sean recomendados por el fabricante.
7. El aparato eléctrico debe ser montado a la pared o al techo sólo como sea recomendado por el fabricante.
8. Servicio—El usuario no debe intentar dar servicio al equipo eléctrico más allá a lo descrito en las instrucciones de operación. Todo otro servicio deberá ser referido a personal de servicio calificado.
9. El aparato eléctrico debe ser situado de tal manera que su posición no interfiera su uso. La colocación del aparato eléctrico sobre una cama, sofá, alfombra o superficie similar puede bloquea la ventilación, no se debe colocar en libreros o gabinetes que impidan el flujo de aire por los orificios de ventilación.
10. El equipo eléctrico deber ser situado fuera del alcance de fuentes de calor como radiadores, registros de calor, estufas u otros aparatos (incluyendo amplificadores) que producen calor.
11. El aparato eléctrico deberá ser conectado a una fuente de poder sólo del tipo descrito en el instructivo de operación, o como se indique en el aparato.
12. Precaución debe ser tomada de tal manera que la tierra física y la polarización del equipo no sea eliminada.
13. Los cables de la fuente de poder deben ser guiados de tal manera que no sean pisados ni pellizcados por objetos colocados sobre o contra ellos, poniendo particular atención a los contactos y receptáculos donde salen del aparato.
14. El equipo eléctrico debe ser limpiado únicamente de acuerdo a las recomendaciones del fabricante.
15. En caso de existir, una antena externa deberá ser localizada lejos de las líneas de energía.
16. El cable de corriente deberá ser desconectado del cuando el equipo no sea usado por un largo periodo de tiempo.

17. Cuidado debe ser tomado de tal manera que objetos líquidos no sean derramados sobre la cubierta u orificios de ventilación.
18. Servicio por personal calificado deberá ser provisto cuando:
 - A: El cable de poder o el contacto ha sido dañado; u
 - B: Objetos han caído o líquido ha sido derramado dentro del aparato; o
 - C: El aparato ha sido expuesto a la lluvia; o
 - D: El aparato parece no operar normalmente o muestra un cambio en su desempeño; o
 - E: El aparato ha sido tirado o su cubierta ha sido dañada.

Safety Notice

Please read and follow the safety instructions to protect yourself from possible injury and to minimize the risk of damage to the unit.

- Follow all instructions and warnings marked on the unit.
- Do not attempt to service the unit yourself, except where explained in this manual.
- Provide proper ventilation and air circulation and do not use near water.
- Keep objects that might damage the device away from it, and place the unit on stable surfaces.
- Only use the power adapter, power cords, and connection cables designed for the unit.
- Do not use liquid or aerosol cleaners to clean this unit. Always unplug the power to the device before cleaning.

Table of Contents

Table of Contents

1. Specifications	7
2. Overview	9
2.1 Introduction	9
2.2 Features	9
2.3 What's Included	9
2.4 Hardware Description	10
3. Connection Diagram	12
4. OSD Menu	13
5. Operation	15
6. Troubleshooting	22
6.1 Contacting Black Box	22
6.2 Shipping and Packaging	22

1. Specifications

Approvals	CE, FCC
Audio Support	Stereo PCM (48 kHz only)
Maximum Resolution	1080p, 1920 x 1200
Maximum Color	4:2:2
Enclosure	Metal wall mounting case with screws
ESD Protection	Human body model: ±19 kV (air-gap discharge) and ±12 kV (contact discharge); Core chipset: ±2 kV
Firmware Update	via USB Port
Frequency Bandwidth	Output video: 165 MHz; Input video: 74.25 MHz
IR Sensor	Receives IR commands from the IR remote
User Controls	(1) DIP switch for firmware update; (3) Push buttons (Down, Up, Menu/Enter)
Connectors	Input: (1) HDMI Type A (19-pin female), Output: (2) 3.5-mm stereo (L, R), (3) RCA (YPbPr), (1) RCA (CVBS), (1) RCA (S/PDIF); Firmware update and control: (1) Mini USB; Power: (1) interlocking power jack
Indicators	(1) Red LED for Power; (1) Green LED for Video Signal

Chapter 1: Specifications

1. Specifications (continued)

Environment	Temperature Tolerance: Operating: 32 to 104° F (0 to 40° C); Storage: -4 to +140° F (-20 to +60° C) Relative Humidity: 20–90%, noncondensing
Power	Power supply: 5 VDC, 2 A; Consumption: 5 Watts (max.)
Dimensions	5.3"H x 6.9"W x 5"D (13.5 x 17.5 x 12.7 cm)
Weight	9.5 oz. (270 g)

2. Overview

2.1 Introduction

Scalers work to convert and scale a type of video/audio signal to another type of video/audio signal. This enables you to use differently formatted video/audio signals on differently formatted display screens. Scaling allows for changing resolutions to increase quality or improve compatibility.

The HDMI to Video Scaler and Converter (AVSC-HDMI-VIDEO) converts digital HDMI to Component/CVBS with either digital audio (S/PDIF) or analog stereo audio. With this module, HDMI based devices such as Blu-ray disc players, PS3, DVD players, camcorders, or set-top boxes can connect to your PC LCD and PC speakers. The device also enables users to connect full digital video and audio to a CVBS monitor and S/PDIF equipped audio receiver and amplifier for maximum compatibility with your home theater devices.

2.2 Features

- IR remote control
- Remote control via Mini-USB
- OSD control interface
- Input maximum pixel rate: 165 MHz
- Deinterlacer supported
- Supports noise reduction and video enhancement features
- Over/under scanning adjustable
- Video H/V mirror supported
- Active video area adjustment supported
- USB firmware upgradable for expanding compatibility
- Wallmount housing design for easy installation

2.3 What's Included

- HDMI to Video Scaler and Converter
- 5-VDC, 2-A power supply unit
- IR Remote control
- This User's Manual
- Installation software CD (CD included; you can also download installation software from blackbox.com).

Chapter 2: Overview

2.4 Hardware Description

Figures 2-1 and 2-2 show the front and back panels of the scaler. Table 2-1 describes its components.



Figure 2-1. Front panel.



Figure 2-2. Back panel.

Table 2-1. Scaler components.

Number	Component	Description
1	CVBS	Connects to as CVBS display with a CVBS male-male cable
2, 3	(2) Stereo audio out connectors (1 L, 1 R)	Connects to analog stereo audio speaker.
4	DIP switch	For firmware update: ON (UP): firmware update mode; OFF (DOWN): normal mode
5	LED indicator	(1) Red LED for Power; (1) Green LED for Video Signal
6	IR sensor	Used to receive the IR commands from IR remote
7	Push button	Down button
7	Push button	Up button
7	Push button	Menu/Enter button
5	(2) LED indicators	(1) Power LED (red)
8	Interlocking power jack	Connects to 5 VDC power supply unit
9	Mini-USB port	<ul style="list-style-type: none"> • Used for firmware update • Connects to 5 VDC power supply unit
10	S/PDIF Audio out connector	Connects to digital S/PDIF audio speaker
11, 12, 13	(3) Component output connectors	Component output (Y, Pb, Pr)
14	HDMI IN connector	Connect to a HDMI source

Chapter 3: Connection Diagram

3. Connection Diagram




Figure 3-1. Typical application.

4. OSD Menu

Table 4-1. OSD menu.

Option	Description	Settings
1. Output Setup	Output Mode	YCbCr4:2:2
	Default Pattern	Disable (Default); White; Cross; Hatch; Color; Gray; Windows; H-Ramp; W-HRamp; W-VRamp; Diagonal
	EDID Audio CH#	2ch, 7.1ch
2. Image	Contrast	0–255 (Default = 0)
	Brightness	0–255 (Default = 0)
	Saturation	0–255 (Default = 0)
	Hue	0–255 (Default = 0)
	B/W Extension	Off (Default)
		On
	Color Tone	Off (Default)
		Skin
		Green
Edge Enhance	Typ, Med, Max, Off	
Sharpness	0–127 of Sharpness level	

Chapter 4: OSD Menu

Table 4-1 (continued). OSD menu.

Option	Description	Settings
3. Adjustment	Under/Over Scan	-50%–50% (Default Off)
	Aspect Ratio	16:9 (Default); 4:3
	H-Mirror	Off (Default); On
	V-Mirror	Off (Default); On
	H-Shift	-100–100 (Default 0)
	V-Shift	-50–50 (Default 0)
4. System	Input Res. Info	
	Firmware Version	
	Factory Reset	No (Default); Yes

5. Operation

Method A: Push-in Button

See Figure 5-1.



Figure 5-1. Location of push buttons on the scaler.

Method B: IR Remote Control




Figure 5-2. Remote control.

Chapter 5: Operation

Table 5-1. IR remote control functions.

Button	Function
FREEZE	Freeze video
ASPECT RATIO	Aspect ratio change
BLANK	Blank video
EXIT	Exit OSD
ENTER	Enter key
UP	Up key
LEFT	Left key
RIGHT	Right key
DOWN	Down key
MENU	Menu on
INPUT INFO	Source resolution information
1080p60	Select 1080p60 output resolution
1080i60	Select 1080i60 output resolution
720p60	Select 720p60 output resolution
480p60	Select 480p60 output resolution

Method C: IR Remote Control through Mini-USB port




Figure 5-3.

Table 5-2. IR remote control through mini-USB port screen functions.

Number in Figure 5-3	Function
1	COM Port Selection
2	COM Port Detection Button
3	Output Setup Button
4	Image Button
5	Adjustment Button
6	System Button
7	Input/Output Resolution Info
8	Refresh Input/Output Resolution Info Button
9	Output Quick Selection Button

Chapter 5: Operation

1. COM Port Selection

Please select the COM PORT application.




Figure 5-4. Select COM port.

2. COM Port Detection Button

Click on the curved-arrow button  to detect the COM PORT.

3. Output Setup Button




Figure 5-5.

4. Image Button




Figure 5-6.

5. Adjustment Button




Figure 5-7.

Chapter 5: Operation

6. System Button




Figure 5-8. System screen.

1) In-Sync Info:

To view the current input resolution

2) Factory Reset Button

3) Firmware Update Button




Figure 5-9. Firmware update screen.

Follow these steps to update the firmware:

STEP A: Unplug the Mini-USB connector from the device.

STEP B: Set the DIP switch to ON (UP).

STEP C: Connect the device to the PC via a USB to mini-USB cable.

STEP D: Click the FW Update button in the software.

STEP E: Click on the "Load File" button to select the firmware file.

STEP F: Click on the "Burn" button to start the firmware update process.

STEP G: Unplug the Mini-USB connector from the device.

STEP H: Set the DIP switch to OFF (DOWN).

The firmware update process is complete.

7. I/O Port and Resolution Info

Displays the information about the I/O Port and the applied resolution.

8. Refresh Button

Refreshes the status of the converter.

9. Output Quick Selection Button

Controls common functions for quick setting.

6. Troubleshooting

6.1 Contacting Black Box

If you determine that your HDMI to Video Scaler and Converter is malfunctioning, do not attempt to alter or repair the unit. It contains no user-serviceable parts. Contact Black Box Technical Support at 724-746-5500 or info@blackbox.com.

Before you do, make a record of the history of the problem. We will be able to provide more efficient and accurate assistance if you have a complete description, including:

- the nature and duration of the problem.
- when the problem occurs.
- the components involved in the problem.
- any particular application that, when used, appears to create the problem or make it worse.

6.2 Shipping and Packaging

If you need to transport or ship your HDMI to Video Scaler and Converter:

- Package it carefully. We recommend that you use the original container.
- If you are returning the unit, make sure you include everything you received with it. Before you ship for return or repair, contact Black Box to get a Return Authorization (RA) number.

Black Box Tech Support: FREE! Live. 24/7.

Tech support the
way it should be.



Great tech support is just 60 seconds away
at 724-746-5500 or blackbox.com.



About Black Box

Black Box provides an extensive range of networking and infrastructure products. You'll find everything from cabinets and racks and power and surge protection products to media converters and Ethernet switches all supported by free, live 24/7 Tech support available in 60 seconds or less.

© Copyright 2014. Black Box Corporation. All rights reserved.

AVSC-HDMI-VIDEO, version 2

724-746-5500 | blackbox.com