



Benefits

- ▶ 1U 17" / 19" LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 1280 x 1024 native resolution / 16.7M colors
- ▶ 104-key keyboard with touchpad
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- DVI-D / HDMI 1.2 video input
- S-Video + Composite (BNC)
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available

Product Specifications

Console Port	
Video input	VGA
KB / MS	USB interface
VGA console 6ft cable : CB-6A	Drawer end : DB-15 + USB type A x 2 Server end : DB-15 + USB type A x 2

Video Option		
Digital	DVI	DVI-D single link
	HDMI	HDMI 1.2 / HDCP 1.1
Analog	S-Video (4-pin)	NTSC & PAL
	Composite (BNC)	NTSC & PAL

LCD Panel	D117	D119
Panel size (diagonal)	17"	19"
Native resolution	1280 x 1024	1280 x 1024
Brightness (cd/m ²)	250	250
Contrast ratio (typ.)	1000 : 1	1000 : 1
Colors	16.7 M	16.7 M
Viewing angle (L/R/U/D)	85/85/80/80	85/85/80/80
Response time (ms)	5	5
Dot pitch (mm)	0.264	0.294
Display area (mm)	337.92H x 270.33V	376.32H x 270.33V
Surface treatment	Haze 25%, Hard-coating	
Surface hardness	3H	
Backlight type	LED	
MTBF (hrs)	30,000	

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 22W / Max. 55W
	Power saving mode	Max. 2W / Max. 34W
	Power button off	Max. 1W / Nil

Physical		D117	D119
Product (W x D x H)	Single console	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch
	Console w/ KVM	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch
Packing (W x D x H)	Single console /	595 x 860 x 140 mm	595 x 860 x 140 mm
	Console w/ KVM	23.4 x 33.9 x 5.5 inch	23.4 x 33.9 x 5.5 inch
Net weight	Single console	12.6 kg / 27.7 lb	13.2 kg / 29 lb
	Console w/ KVM	13.6 kg / 29.9 lb	14.2 kg / 31.2 lb
Gross weight	Single console	18.4 kg / 40.5 lb	19 kg / 41.8 lb
	Console w/ KVM	19.8 kg / 43.6 lb	20.4 kg / 44.9 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance	D117	D119
Single console drawer / Console w/ KVM drawer	660 ~ 870 mm 26 ~ 34.3 inch	660 ~ 870 mm 26 ~ 34.3 inch


Compliance	
EMC	FCC & CE certified
Safety	c UL us & CE / LVD certified
Environment	RoHS3 & REACH compliant

D117 / D119 models w/ KVM

X stands for 17" or 19" LCD size.

2K KVM	IP	Remote	8-port
	0	0	D11X - 801D

2K KVM Cable



CH - 6D (6 ft)
DVI-D KVM cable




CH - 6H (6 ft)
HDMI KVM cable

Resolution: 16:9 - max. 2560 x 1440
Support **: 16:10 - max. 1920 x 1200
4:3 - max. 1600 x 1200

DVI-D KVM	IP	Remote	12-port
	0	0	D11X - 1201D

DVI-D USB KVM Cable




Resolution: 16:10 - max. 1920 x 1200
Support **: 16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200


CI - 6 (6 ft)
CI - 15 (15 ft)

Cat6 Matrix KVM	IP	Remote	8-port	16-port	32-port
	1	1	-	D11X - MUIP1613	D11X - MUIP3213
	2	1	-	D11X - MUIP1624	D11X - MUIP3224
	0	1	-	D11X - MU1602	D11X - MU3202
	0	2	-	D11X - MU1603	D11X - MU3203
	0	3	-	D11X - MU1604	D11X - MU3204


Cat6 KVM Dongle




DG - 100C
USB-C dongle




DG - 100P
DP - USB dongle



DG - 100H
HDMI - USB dongle



DG - 100SD
DVI - USB dongle




DG - 100S
VGA - USB dongle

Resolution: 16:10 - max. 1920 x 1200
Support **: 16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200


Cat6 Combo KVM	IP	Remote	8-port	16-port	32-port
	1	0	D11X - UIP802	D11X - UIP1602	D11X - UIP3202
	0	1	D11X - U802	D11X - U1602	D11X - U3202
	0	0	D11X - U801	D11X - U1601	D11X - U3201

DB-15 Matrix KVM	IP	Remote	8-port	16-port
	1	1	D11X - MIP813	D11X - MIP1613
	2	1	D11X - MIP824	D11X - MIP1624
	0	1	D11X - M802	D11X - M1602
	0	2	D11X - M803	D11X - M1603
	0	3	D11X - M804	D11X - M1604


DB-15 VGA USB KVM Cable



CB - 6 (6 ft)



CB - 10 (10 ft)





CB - 15 (15 ft)

Resolution: 16:10 - max. 1920 x 1200
Support **: 16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200


DB-15 Combo KVM	IP	Remote	8-port	16-port
	1	0	D11X - IP802	D11X - IP1602
	0	1	D11X - 802	D11X - 1602
	0	0	D11X - S801	D11X - S1601






Standard Keyboard



Ge G keyboard integrated with touchpad



Supporting layouts

America  United States

EMEA  United Kingdom  Germany  France  Spain  Italy

Asia  Japan  Korea

Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Se S keyboard with touchpad

